

# OMNIDECK™ LD

## PRODUCT SPECIFICATIONS

<b>MODULE SIZE</b>	<p><b>Actual</b> 6 ft (L) x 3 ft (W) x 1.5 in (H) 1.8 m x 0.9 m x 3.8 cm</p> <p><b>Usable Surface Area</b> 18 ft<sup>2</sup> (1.67 m<sup>2</sup>)</p>
<b>WEIGHT</b>	36 lbs (16.3 kg)
<b>COLOR</b>	Translucent, anthracite gray
<b>MATERIAL</b>	High-Density Polyethylene (HDPE) with UV resistance properties and polycarbonate cam locks
<b>WEIGHT CAPACITY</b>	200 psi, depending on subsurface conditions
<b>FLAMMABILITY RESISTANCE</b>	UL94HB
<b>AERATION / DRAINAGE / LIGHT PENETRATION</b>	1.88 in <sup>2</sup> / ft <sup>2</sup>
<b>CONNECTION SYSTEM</b>	<p>Interlocking puzzle-piece panel design</p> <p>Built-in cam locks secure adjoining panels with the twist of a t-bar tool</p>
<b>SHIPPING INFO</b>	<p>U.S. standard truck: 840 panels</p> <p>40 ft ISO shipping container: 648 panels</p> <p>20 ft ISO shipping container: 312 panels</p> <p>UK lorry: 868 panels</p>